



# FH67P | Branches 36 (Custom)

## DESIGN

---

Product Type	Synthesis - PDI (Precision Dye Injection)
Construction	Tufted - custom 1500 sq yd minimum
Surface Texture	Textured Patterned Cut & Loop
Gauge	1/10"
Stitches Per Inch	12.2
Dye Method	Precision Dye Injection
Backing Material	Wedlok <sup>®</sup>
Fiber Type	Colorstrand <sup>®</sup> Nylon
Tufted Face Weight	36.00 oz per sq yd
Pile Thickness	0.293
Density	4,423
Weight Density	159,235
Product Thickness (Wedlok)	0.386
Product Thickness (Wedlok Air)	0.551
Width	12', 13'6", 15'
Soil Release Technology	Sentry

## SUSTAINABILITY

---

Iaq Green Label Plus	6678
Pre Consumer Recycled Content	50%
Nsf 140	Gold
Declare Label	Declared

## PERFORMANCE

---

Static	Less than 3.5 K.V.
Flammability	Meets or exceeds requirement Class 1
Smoke Density	450 or Less

## SERVICE

---

Warranties	10 Year Limited Wear Warranty, Lifetime Static
------------	--

**DURKAN**

contact us: 800.241.4580 tech services: 800.833.6954 durkan.com a division of **Mohawk Group**