



# FH82P | Watermark 32 (Custom)

## DESIGN

---

Product Type	Synthesis - PDI (Precision Dye Injection)
Construction	Tufted - custom 1500 sq yd minimum
Surface Texture	Textured Patterned Cut & Loop
Gauge	1/10"
Stitches Per Inch	11.1
Dye Method	Precision Dye Injection
Backing Material	Wedlok <sup>®</sup>
Fiber Type	Colorstrand <sup>®</sup> Nylon
Tufted Face Weight	32.00 oz per sq yd
Pile Thickness	0.218
Density	5,284
Weight Density	169,101
Product Thickness (Wedlok)	0.311
Product Thickness (Wedlok Air)	0.476
Width	12', 13'6", 15'

## SUSTAINABILITY

---

Iaq Green Label Plus	6678
Pre Consumer Recycled Content	51%
Nsf 140	Gold
Declare Label	Declared

## PERFORMANCE

---

Static	Less than 3.5 K.V.
Flammability	Meets or exceeds requirement Class 1
Smoke Density	450 or Less

## SERVICE

---

Warranties	10 Year Limited Wear Warranty, Lifetime Static
------------	--

**DURKAN**

contact us: 800.241.4580 tech services: 800.833.6954 durkan.com a division of **Mohawk Group**