



# DY48X | Definity Textured 48

## DESIGN

---

Product Type	Definity
Construction	Tufted
Surface Texture	Textured Patterned Cut & Loop
Gauge	1/12"
Stitches Per Inch	11.0
Backing Material	Weldlok <sup>®</sup>
Fiber Type	Colorstrand <sup>®</sup> SD Nylon
Tufted Face Weight	48.00 oz per sq yd
Pile Thickness	0.36
Density	4,800
Weight Density	230,400
Product Thickness (Wedlok)	0.453
Product Thickness (Wedlok Air)	0.618
Width	12', 13'6", 15'
Soil Release Technology	Sentry

## SUSTAINABILITY

---

Iaq Green Label Plus	8216
Pre Consumer Recycled Content	48%
Nsf 140	Gold
Declare Label	Declared

## PERFORMANCE

---

Static	Less than 3.5 K.V.
Flammability	Meets or exceeds requirement Class 1
Smoke Density	450 or Less

## SERVICE

---

Warranties	Lifetime Limited Weldlok Warranty, Lifetime Limited Colorfastness to Light, 10 year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static
------------	--

**DURKAN**

contact us: 800.241.4580 tech services: 800.833.6954 durkan.com a division of **Mohawk Group**