



DY54X | Definity Textured 54

DESIGN

Product Type	Definity
Construction	Tufted
Surface Texture	Textured Patterned Cut & Loop
Gauge	1/14"
Stitches Per Inch	12.0
Backing Material	Weldlok [®]
Fiber Type	Colorstrand [®] SD Nylon
Tufted Face Weight	54.00 oz per sq yd
Pile Thickness	0.372
Density	5,226
Weight Density	282,194
Product Thickness (Wedlok)	0.465
Product Thickness (Wedlok Air)	0.63
Width	12', 13'6", 15'
Soil Release Technology	Sentry

SUSTAINABILITY

Iaq Green Label Plus	8216
Pre Consumer Recycled Content	49%
Nsf 140	Gold
Declare Label	Declared

PERFORMANCE

Static	Less than 3.5 K.V.
Flammability	Meets or exceeds requirement Class 1
Smoke Density	450 or Less

SERVICE

Warranties	Lifetime Limited Weldlok Warranty, Lifetime Limited Colorfastness to Light, 10 year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static
------------	--

DURKAN

contact us: 800.241.4580 tech services: 800.833.6954 durkan.com a division of **Mohawk Group**