



DY60X | Definity Textured 60

DESIGN

Product Type	Definity
Construction	Tufted
Surface Texture	Textured Patterned Cut & Loop
Gauge	1/14"
Stitches Per Inch	14.0
Backing Material	Weldlok [®]
Fiber Type	Colorstrand [®] SD Nylon
Tufted Face Weight	60.00 oz per sq yd
Pile Thickness	0.366
Density	5,902
Weight Density	354,098
Product Thickness (Wedlok)	0.459
Product Thickness (Wedlok Air)	0.624
Width	12', 13'6", 15'
Soil Release Technology	Sentry

SUSTAINABILITY

Iaq Green Label Plus	8216
Pre Consumer Recycled Content	46%
Nsf 140	Gold
Declare Label	Declared

PERFORMANCE

Static	Less than 3.5 K.V.
Flammability	Meets or exceeds requirement Class 1
Smoke Density	450 or Less

SERVICE

Warranties	Lifetime Limited Weldlok Warranty, Lifetime Limited Colorfastness to Light, 10 year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static
------------	--

DURKAN

contact us: 800.241.4580 tech services: 800.833.6954 durkan.com a division of **Mohawk Group**