



# PP363C | Pattern Perfect 3 Color

## DESIGN

---

Product Type	Broadloom
Construction	Tufted
Minimum Sq Yd	500 sq yds
Surface Texture	Textured Tip-Shear Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Stitches Per Inch	9.0 (35.43 rows per 10 cm)
Dye Method	Solution Dyed
Backing Material	Weldlok®
Fiber Type	Colorstrand® Nylon
Tufted Face Weight	36 oz/yd2 (1,221 g/m2)
Pattern Repeat	TBD
Width	12' width (3.66 m)
Soil Release Technology	EcoSentry Soil
Stain Release Technology	0
IAQ Green Label Plus	8216
NSF 140	Gold
Declare Label	Declared

## PERFORMANCE

---

Static	AATCC-134 Under 3.5 KV
Foot Traffic Recommendation	Heavy
GSA Stain Release Rating	Pass
Flammability	ASTM E 648 Class I (Glue Down)
Smoke Density	ASTM E 662 Less than 450

## SERVICE

---

Warranties	Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static
------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**DURKAN**

contact us: 800.241.4580 tech services: 800.833.6954 durkan.com a division of **Mohawk Group**