



PP384C | Pattern Perfect 4 Color

DESIGN

Product Type	Broadloom
Construction	Tufted
Minimum Sq Yd	500 sq yds
Surface Texture	Textured Tip-Shear Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Stitches Per Inch	9.0 (35.43 rows per 10 cm)
Dye Method	Solution Dyed
Backing Material	Weldlok®
Fiber Type	Colorstrand® Nylon
Tufted Face Weight	38 oz/yd2 (1,288 g/m2)
Pattern Repeat	TBD
Width	12' width (3.66 m)
Soil Release Technology	EcoSentry Soil
Stain Release Technology	EcoSentry Plus Stain
IAQ Green Label Plus	8216
NSF 140	Gold
Declare Label	Declared

PERFORMANCE

Static	AATCC-134 Under 3.5 KV
Foot Traffic Recommendation	Heavy
GSA Stain Release Rating	Pass
Flammability	ASTM E 648 Class I (Glue Down)
Smoke Density	ASTM E 662 Less than 450

SERVICE

Warranties	Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static
------------	---

DURKAN

contact us: 800.241.4580 tech services: 800.833.6954 durkan.com a division of **Mohawk Group**