



# FH69P | Altostratus 36 (Custom)

## DESIGN

---

Product Type	Synthesis - PDI (Precision Dye Injection)
Construction	Tufted - custom 1500 sq yd minimum
Surface Texture	Textured Patterned Cut & Loop
Gauge	1/10"
Stitches Per Inch	12.1
Dye Method	Precision Dye Injection
Backing Material	Weldlok®
Fiber Type	Colorstrand® Nylon
Tufted Face Weight	36.00 oz per sq yd
Pile Thickness	0.294
Density	4,408
Weight Density	158,694
Product Thickness (Wedlok)	0.387
Product Thickness (Wedlok Air)	0.552
Width	12', 13'6", 15'
Soil Release Technology	Sentry

## SUSTAINABILITY

---

Iaq Green Label Plus	6678
Pre Consumer Recycled Content	50%
Nsf 140	Gold
Declare Label	Declared

## PERFORMANCE

---

Static	Less than 3.5 K.V.
Flammability	Meets or exceeds requirement Class 1
Smoke Density	450 or Less

## SERVICE

---

Warranties	10 Year Limited Wear Warranty, Lifetime Static
------------	--

**DURKAN**

contact us: 800.241.4580 tech services: 800.833.6954 durkan.com a division of **Mohawk Group**