



DY60X | Definity Textured 60

DESIGN

| | |
|--------------------------------|-------------------------------|
| Product Type | Definity |
| Construction | Tufted |
| Surface Texture | Textured Patterned Cut & Loop |
| Gauge | 1/14" |
| Stitches Per Inch | 14.0 |
| Backing Material | Weldlok® |
| Fiber Type | Colorstrand® SD Nylon |
| Tufted Face Weight | 60.00 oz per sq yd |
| Pile Thickness | 0.366 |
| Density | 5,902 |
| Weight Density | 354,098 |
| Product Thickness (Wedlok) | 0.459 |
| Product Thickness (Wedlok Air) | 0.624 |
| Width | 12', 13'6", 15' |
| Soil Release Technology | Sentry |

SUSTAINABILITY

| | |
|-------------------------------|----------|
| Iaq Green Label Plus | 8216 |
| Pre Consumer Recycled Content | 46% |
| Nsf 140 | Gold |
| Declare Label | Declared |

PERFORMANCE

| | |
|---------------|--------------------------------------|
| Static | Less than 3.5 K.V. |
| Flammability | Meets or exceeds requirement Class 1 |
| Smoke Density | 450 or Less |

SERVICE

| | |
|------------|--|
| Warranties | Lifetime Limited Weldlok Warranty, Lifetime Limited Colorfastness to Light, 10 year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static |
|------------|--|

DURKAN

contact us: 800.241.4580 tech services: 800.833.6954 durkan.com a division of **Mohawk Group**